

[illegible]

Part #	Part Code	Fredsert Data					Installation Data								
		A	B	C	D	P	Q	R	S	T	U	V			
		ID Thread	Minimum Effective ID Thread Depth (mm)	Overall Length (mm)	Head Dia (mm)	Head Thickness (mm)	Min C bore Dia (mm)	Min C bore Depth (mm)	Class 6H Thread in Parent Material	Min Drill Depth (mm)	Min Thread Depth (mm)	Tap Drill Diameter (mm)	Drive Tool	Combo Tool	Install Torque (ft-lbs)
GBAMRT610-12175-9T-50	692	M6X1.0	THRU	59.00	18.48	50.00	N/A	N/A	M12 x 1.75	11.50	9.00	10.20	16 mm HEX	C7	110
GBAMRT610-12175-9S-35	669	M6X1.0	18	44.00	18.48	35.00	N/A	N/A	M12 x 1.75	11.50	9.00	10.20	16 mm HEX	C7	110
GBAMRT610-12175-9S-77	673	M6X1.0	18	86.00	18.48	77.00	N/A	N/A	M12 x 1.75	11.50	9.00	10.20	16 mm HEX	C7	110
BAMRT610-12175-9T-15	677	M6X1.0	THRU	24.00	18.48	15.00	N/A	N/A	M12 x 1.75	11.50	9.00	10.20	16 mm HEX	C7	110
GBAMRT610-12175-9T-20	682	M6X1.0	THRU	29.00	18.48	20.00	N/A	N/A	M12 x 1.75	11.50	9.00	10.20	16 mm HEX	C7	110
GBAMRT610-12175-9T-27	686	M6X1.0	THRU	36.00	18.48	27.00	N/A	N/A	M12 x 1.75	11.50	9.00	10.20	16 mm HEX	C7	110
GBAMRT610-12175-9T-35	689	M6X1.0	THRU	49.00	18.48	35.00	N/A	N/A	M12 x 1.75	11.50	9.00	10.20	16 mm HEX	C7	110
GBAMRT8125-1420-11T-16	702	M8X1.25	THRU	27.00	20.79	16.00	N/A	N/A	M14 x 2.0	13.50	11.00	12.00	18 mm HEX	C12	130
GBAMRT8125-1420-11T-28	707	M8X1.25	THRU	39.00	20.79	28.00	N/A	N/A	M14 x 2.0	13.50	11.00	12.00	18 mm HEX	C12	130
GBAMRT8125-1420-11S-64	695	M8X1.25	15	75.00	20.79	64.00	N/A	N/A	M14 x 2.0	13.50	11.00	12.00	18 mm HEX	C12	130
GBAMRT8125-1420-11T-14	699	M8X1.25	THRU	25.00	20.79	14.00	N/A	N/A	M14 x 2.0	13.50	11.00	12.00	18 mm HEX	C12	130
GBAMRT8125-1420-11T-23	705	M8X1.25	THRU	34.00	20.79	23.00	N/A	N/A	M14 x 2.0	13.50	11.00	12.00	18 mm HEX	C12	130
GBAMRT8125-1420-11T-8	708	M8X1.25	THRU	18.89	20.79	7.89	N/A	N/A	M14 x 2.0	13.50	11.00	12.00	18 mm HEX	C12	130
GBAMRT8125-1420-11S-68	697	M8X1.25	15	79.00	20.79	68.00	N/A	N/A	M14 x 2.0	13.50	11.00	12.00	18 mm HEX	C12	130
GBAMRT8125-1420-11T-15	701	M8X1.25	THRU	26.00	20.79	15.00	N/A	N/A	M14 x 2.0	13.50	11.00	12.00	18 mm HEX	C12	130
GBAMRT8125-1420-11T-24	706	M8X1.25	THRU	35.00	20.79	24.00	N/A	N/A	M14 x 2.0	13.50	11.00	12.00	18 mm HEX	C12	130
GBAMRT8125-1620-145S-100	709	M8X1.25	15	114.5	20.79	100.00	N/A	N/A	M14 x 2.0	17.50	14.50	14.00	20 mm HEX	C58	225
GBAMRT8125-1420-11S-100	693	M8X1.25	15	111.00	20.79	100.00	N/A	N/A	M14 x 2.0	13.50	11.00	12.00	18 mm HEX	C12	130
GBAMRT8125-1420-11T-11	698	M8X1.25	THRU	22.14	20.79	11.14	N/A	N/A	M14 x 2.0	13.50	11.00	12.00	18 mm HEX	C12	130
GBAMRT1015-1620-145S-12	649	M10X1.5	16	26.50	23.10	12.00	N/A	N/A	M16 x 2.0	17.00	14.50	14.00	20 mm HEX	C58	225
GBAMRT1015-1620-145T-28	652	M10X1.5	THRU	42.50	23.10	28.00	N/A	N/A	M16 x 2.0	17.00	14.50	14.00	20 mm HEX	C58	225
GBAMRT1015-1620-145T-10	650	M10X1.5	THRU	24.50	23.10	10.00	N/A	N/A	M16 x 2.0	17.00	14.50	14.00	20 mm HEX	C58	225
GBAMRT1015-1620-145T-5	653	M10X1.5	THRU	19.50	23.10	5.00	N/A	N/A	M16 x 2.0	17.00	14.50	14.00	20 mm HEX	C58	225

[illegible]