

Weld Boss Style - Inch

Part #	ID Thread (A)	Thread Length (B)	OAL (C)	Boss Dia. (D)	Boss Height (P)	Pilot Dia. (D1)	Bore	Mat'l
10551751-SL	10-32 UNF-2B	0.38	1.17	0.75	0.98	0.5 THRU	AL	
110669866-001-SL	10-32 UNF-2B	0.38	1.17	1	0.98	0.8 THRU	STL	
10504758-SL	.125 NPT	0.25	0.57	0.75	0.38	0.5 THRU	AL	
10504999-SL	.125 NTP	0.25	0.57	0.75	0.38	0 THRU	STL	
10551959-SL	.125 NTP	0.25	0.69	1.25	0.5	1 THRU	STL	
10553970-SL	.125-27 NPTF	0.25	0.57	0.75	0.38	0.5 THRU	CRES	
10511938-SL	.250-18 NPTF	0.5	0.78	0.75	0.59	0.5 THRU	STL	
10503854-SL	.250-18 NPTF	0.25	0.57	0.75	0.38	0.5 THRU	CRES	
10553970-SL	.125-27 NPSF	0.25	0.57	0.75	0.38	0.5 THRU	CRES	
10511838-SL	.250-18 NPTF	0.5	0.78	0.75	0.59	0.5 THRU	STL	
1053854-SL	.250-18 NPTF	0.5	0.63	1	0.44	0.8 THRU	AL	
10504723-SL	.250-18 NPTF	0.5	0.63	1	0.44	0.8 THRU	AL	
10551964-1-SL	.250-20 NPTF	0.5	0.98	0.63	0.79	0.4 THRU	STL	
10552427-1-SL	.250-20 UNC-2B	0.5	0.98	0.63	0.79	0.4 THRU	CRES	
10551968-1-SL	.250-20 UNC-2B	0.5	0.94	0.75	0.75	0.5 THRU	AL	
10526253-SL	.250-20 UNC-2B	0.5	1.06	0.63	0.87	0.4 THRU	CRES	
10527347-SL	.250-20 UNC-2B	0.5	0.78	0.63	0.59	0.4 THRU	CRES	
10527816-SL	.250-20 UNC-2B	0.5	1.06	0.63	0.87	0.4 THRU	CRES	
10550908-SL	.250-20 UNC-2B	0.5	0.58	0.63	0.39	0.4 THRU	CRES	
10551770-SL	.250-20 UNC-2B	0.5	1.17	0.63	0.39	0.4 THRU	STL	
10626094-SL	.250-20 UNC-2B	0.5	0.58	0.63	0.39	0.4 THRU	STL	
10608512-SL	.250-20 UNC-2B	0.5	1.08	1	0.89	0.8 THRU	STL	
10608570-SL	.250-20 UNC-2B	0.5	0.68	1	0.49	0.8 THRU	STL	
10527087-SL	.250-28 UNC-2B	0.5	0.94	0.75	0.75	0.5 THRU	STL	
10550948-SL	.250-28 UNC-2B	0.5	0.94	0.75	0.75	0.5 THRU	CRES	
10511850-SL	.25-18 NPT	0.5	0.91	0.53	0.72	0.3 THRU	AL	
10617219-SL	.25-18 NPT	0.5	0.78	0.75	0.59	0.5 THRU	CRES	
10552427-2-SL	.312-18 UNC-2B	0.63	1.1	0.88	0.91	0.6 THRU	CRES	
10554097-SL	.312-18 UNC-2B	0.63	1.88	1	1.69	0.8 THRU	STL	
10551964-2-SL	.312-18 UNC-2B	0.63	1.1	1	0.91	0.8 THRU	STL	
10551968-2-SL	.312-18 UNC-2B	0.63	1.1	1	0.91	0.8 THRU	AL	
10516819-SL	.312-24 UNF-2B	0.63	1.06	0.63	0.87	0.4 THRU	STL	
10511871-SL	.312-24 UNF-2B	0.63	0.9	1	0.71	0.8 THRU	STL	
10516614-SL	.312-24 UNF-2B	0.63	2.16	1	1.97	0.8 THRU	STL	
10516615-SL	.312-24 UNF-2B	0.63	0.69	1	0.5	0.8 THRU	STL	
10550949-SL	.312-24 UNF-2B	0.63	0.94	1	0.75	0.8 THRU	CRES	
10671850-001-SL	.375-24 UNC-2B	0.75	0.86	0.75	0.67	0.5 THRU	STL	
10556858-SL	.375-24 UNC-2B	0.75	0.78	1	0.59	0.8 THRU	CRES	
10657264-SL	.375-16 UNC-2B	0.75	0.78	1	0.59	0.8 THRU	STL	
10551964-3-SL	.375-16 UNC-2B	0.75	1.22	1	1.03	0.8 THRU	STL	
10551968-3-SL	.375-16 UNC-2B	0.75	1.22	1	1.03	0.8 THRU	AL	
10552427-3-SL	.375-16 UNC-2B	0.75	1.22	1	1.03	0.8 THRU	CRES	
10511621-SL	.375-16 NPTF	0.75	0.69	1	0.5	0.8 THRU	AL	
10556898-SL	.375-16 NPTF	0.75	1.77	1.25	1.58	1 THRU	AL	
10556967-SL	.375-16 NPTF	0.75	0.82	1.25	0.63	1 THRU	AL	
10511496-SL	.500 NPTF	1	0.82	1.5	0.63	1.3 THRU	AL	
10511621-SL	.375-18 NPTF	0.75	0.69	1	0.5	0.8 THRU	AL	
10556898-SL	.375-18 NPTF	0.75	1.77	1.25	1.58	1 THRU	AL	
10556967-SL	.375-18 NPTF	0.75	0.85	1.25	0.63	1 THRU	AL	
10511496-SL	.500 NPTF	1	0.82	1.5	0.63	1.3 THRU	AL	
10551964-4-SL	.500-14 UNC-2B	1	1.47	1.25	1.28	1 THRU	STL	
10552427-4-SL	.500-13 UNC-2B	1	1.47	1.25	1.28	1 THRU	CRES	

10551968-4-SL	.500-13 UNC-2B	1	1.47	1.5	1.28	1.3 THRU	AL
10626623-SL	.5625-18 UNC-2B	1.13	0.98	1	0.79	0.8 THRU	AL
10551964-5-SL	.625-11 UNC-2B	1.25	1.72	1.63	1.53	1.4 THRU	STL
10551968-5-SL	.625-11 UNC-2B	1.25	1.72	1.88	1.53	1.6 THRU	AL
10525518-SL	.625-24 UNF-2B	1.25	0.98	1	0.79	0.8 THRU	STL
10551964-6-SL	.75-10 UNC-2B	1.5	1.97	1.88	1.78	1.6 THRU	STL
10551968-6-SL	.75-10 UNC-2B	1.5	1.97	2.25	1.78	2 THRU	AL
10551964-7-SL	1.00-8 UNC-2B	2	2.48	2.5	2.29	2.3 THRU	STL
10551968-7-SL	1.00-8 UNC-2B	2	2.48	3	2.29	2.8 THRU	AL